



KUALA LUMPUR

CONVENTION CENTRE

Plenary Hall Room Specifications

Seating Capacity

- Total seating capacity is 2,994 pax
- Lower tier has 1,973 seats which can be reduced to 1,110 using a mesh curtain
- The AV console area occupies 27 seats
- Upper tier has 944 seats
- Thrust stage has 77 seats

Stage Dimensions

- Proscenium Width 16.900 m
- Proscenium Height 8.850 m
- Stage Width D/stage 21.000 m
- Stage Width U/stage 17.500 m
- Stage Depth 10.275 m
- Grid Height 19.000 m
- Thrust Stage Width 15.500 m
- Thrust Stage Depth 4.150 m
- Loading Door Width 2.220 m
- Loading Door Height 2.300 m
- Stage catwalk Height 9.500 m

Fly Bars

- Number of fly bars 30
- Fly bar load weight 500kg
- House curtain fly bar Bar #1
- Lighting fly bars LX(1>5) Bars #3, 9, 15, 21, 26
- Video Screen fly bar Bar #12
- Cyc/ Black tab (F/A) fly bar Bar #30
- Fly bar control DS/Right
- Legs and Borders 4 sets

Power

- US/Left 1 x 60 amp 3 phase (tap in)
- US/Right 2 x 60 amp 3 phase (tap in)
1 x 32 amp 3 phase Wilco

Lighting

- Strand CD80SV Dimmers (2.4kw, 6.0kw,12.0kw)
- Strand 300 Lighting Control Board
 - LX1 18 circuits
 - LX2 16 circuits
 - LX3 16 circuits
 - LX4 16 circuits
 - LX5 52 circuits
 - DS/Left 24 circuits
 - DS/Right 24 circuits
 - US/Left 24 circuits
 - US/Right 24 circuits
 - FOH Bridge 1 20 circuits
 - FOH Bridge 2 20 circuits
 - FOH Bridge 3 20 circuits
 - Follow Spots 2 x 2kw Ushio Xenon

FOH Rigging Points

- Above Thrust stage 4 x 1 ton

House Lights

- Crestron Wireless control panel (4 levels)

AV Console Area

- Position centre of room under front of circle
- Distance to stage 22.250 m
- Width 5.760 m
- Depth 2.690 m
- Seat loss 27 seats
- Power 6 x 13 amp single phase
- Mike lines 32
- Audio tie lines 16
- Intercom 2

Video

- Projector Barco FLM R22+ 22,000 ANSI Lumens
- Screen Showtex FronScreen Blackout Front Projection Screen (24.6ft x 19.6ft)
- Cameras 4 x Panasonic AW-E750 3-CCD (pan/tilt)
- Switcher Extron ISS 506 Seamless Switcher 6 input
- Procesor Folsom Image Pro HD

Speaker system

- Speakers Proscenium 3 x Meyer MSL-4
3 x Meyer UPA-1P down fill cluster (left, centre and right)
- Bass Speakers 3 x Meyer 650-P (left and right)

House Delay Speakers

- 12 x Meyer UPMs
- 28 x Quad Arena 12" ceiling speakers (Crown Dual Amplifier)
- 52 x Quad Arena 8" ceiling speakers (Crown Dual Amplifier)

LCR balanced line inputs

- Symnet Matrix & Lake Contour Digital Loudspeaker Processors

AV Control Room

- Crestron 5.7" LCD Wireless Touch Control Panel x 1
- Crestron 12" Wired Colour Touch Control Panel x 1
- Acer P4 System (Analogway Show Manager) x 1
- Symnet 8 in/out AD Converter to sound system x 5
- Symnet Break Out DA Converter x 9
- Crown Dual 300 watts/ch @ 4Ω x 1
- Crown Dual 600 watts/ch @ 4Ω x 8
- JBL 4412A 12" Studio Monitors x 2

Talk Back

- Clearcom Loudspeaker 2ch Station with Gooseneck Microphone x 14

Interpretation System

- Iris in-seat interpretation and conference system with voting feature x 802
- Full in-house coverage for interpretation belt pack radiator

Interpreter Room

- 6 x rooms located at the rear of the upper tier